



General Purpose Castors

Steel Framed Castors with Nylon Wheels and Precision Ball Bearings


Fixed castors and swivel castors with steel frames.

Maximum load capacity tested according to BS EN 12532:1999 requirements.



Fixing System	Top plate
Frame	Cold pressed steel plate
Wheel Tread	Nylon 6
Wheel Bearing Type	Double precision ball bearings



Features



Technical Information



Order Code	Load Capacity (in kilograms)	Dimensions (in millimetres)											Physical Mass (in grams)
		$A \times B$	$a_1 \times b_1$	$a_2 \times b_2$	D_{G1}	D	h	d_F	b_{T1}	b_{T2}	D_d	Swept Radius	
NBLK-80	100	105 × 85	80 × 60	72 × 52	9	80	102,5	–	43	32	10	–	465
NBLJ-80	100	105 × 85	80 × 60	72 × 52	9	80	102,5	33	43	32	10	73	595
NBLK-100	125	105 × 85	80 × 60	72 × 52	9	100	125	–	43	35	10	–	580
NBLJ-100	125	105 × 85	80 × 60	72 × 52	9	100	125	36	43	35	10	86	680
NBLK-125	150	105 × 85	80 × 60	72 × 52	9	125	150	–	43	38	10	–	670
NBLJ-125	150	105 × 85	80 × 60	72 × 52	9	125	150	39	43	38	10	101,5	740

Technical information and dimensions provided above are subject to tolerances