



General Purpose Castors

304 Stainless-Steel Framed Heavy-Duty Castors with Nylon Wheels

Fixed castors and swivel castors with steel frames.

Maximum load capacity tested according to BS EN 12532:1999 requirements.



Fixing System	Top plate
Frame	Cold pressed steel plate
Wheel Tread	Nylon 6
Wheel Bearing Type	Plain bore



Features



Technical Information



Order Code	Load Capacity (in kilograms)	Dimensions (in millimetres)											Physical Mass (in grams)
		A × B	a ₁ × b ₁	a ₂ × b ₂	D _{G1}	D	h	d _F	b _{T1}	b _{T2}	D _d	Swept Radius	
NKA-80	100	105 × 85	80 × 60	72 × 52	9	80	105	–	43	32	10	–	420
NJA-80	100	105 × 85	80 × 60	72 × 52	9	80	105	35	43	32	10	75,1	530
NKA-100	125	105 × 85	80 × 60	72 × 52	9	100	125	–	43	35	10	–	485
NJA-100	125	105 × 85	80 × 60	72 × 52	9	100	125	37	43	35	10	87,2	605
NKA-125	150	105 × 85	80 × 60	72 × 52	9	125	150	–	43	38	10	–	620
NJA-125	150	105 × 85	80 × 60	72 × 52	9	125	150	39	43	38	10	101,8	725

Technical information and dimensions provided above are subject to tolerances